



Print		
Maximum Printing Resolution	600 (horizontal) x 1200 (vertical) dpi	
Print Head / Ink	Type:	Individual Ink Cartridges
	Number of Nozzles:	Total 4,352 nozzles
	Ink Cartridge:	PGI-2700 (Cyan, Magenta, Yellow, Black) Optional: PGI-2700XL (Cyan, Magenta, Yellow, Black)
Print Speed* <sup>1</sup> Based on ISO / IEC 24734. Click <a href="#">here</a> for summary report Click <a href="#">here</a> for Document Print and Copy Speed Measurement Conditions	Document: Colour * <sup>1</sup> : ESAT / Simplex	Approx. 15.5ipm
	Document: Colour:	Max. 26.5ppm* <sup>2</sup>
	Document: B / W * <sup>1</sup> : ESAT / Simplex	Approx. 24.0ipm
	Document: B / W:	Max. 32.5ppm* <sup>2</sup>

	Document: Colour <sup>*1</sup> : ESAT / Duplex	Approx. 9.5ipm
	Document: B / W <sup>*1</sup> : ESAT / Duplex	Approx. 13.0ipm
	Document: Colour <sup>*1</sup> : FPOT Ready / Simplex	Approx. 7secs.
	Document: B / W <sup>*1</sup> : FPOT Ready / Simplex	Approx. 6secs.
	Document: Colour <sup>*1</sup> : FPOT Sleep / Simplex	Approx. 12secs.
	Document: B / W <sup>*1</sup> : FPOT Sleep / Simplex	Approx. 10secs.
Printable Width	Up to 203.2mm (8in.)	
Printable Area	Bordered Printing:	Top margin: 3mm, Bottom margin: 5mm, Left / Right margin: each 3.4mm (Letter / Legal: Left: 6.4mm, Right: 6.3mm)
	Bordered Auto Duplex Printing:	Top margin: 3mm, Bottom margin: 5mm, Left / Right margin: each 3.4mm (Letter / Legal: Left: 6.4mm, Right: 6.3mm)
Recommended Printing Area	Top Margin:	45.8mm
	Bottom Margin:	36.8mm
Paper Size	<p>A4, A5, B5, Letter, Legal, Oficio, B-Oficio*, M-Oficio, Foolscap, Legal (India), Executive, 4 x 6", 5 x 7", 8 x 10", Envelopes (DL, COM10, C5, Monarch)</p> <p>Custom size [cassette (upper)]: width 89 - 216.0mm, length 127 - 355.6mm, [cassette (lower)]: width 210 - 216.0mm, length 279.4 - 355.6mm)</p> <p>*Not supported for Mac</p>	

Paper Handling (Cassette 1: Upper) (Maximum Number)	Plain Paper	A4, A5, B5, Letter, Legal = 250
	Photo Paper Pro Luster (LU-101)	A4 = 10
	Matte Photo Paper (MP-101)	4 x 6" = 20, A4 = 10
	Photo Paper Plus Glossy II (PP-201)	4 x 6" = 20, A4 = 10
	Glossy Photo Paper "Everyday Use" (GP-508)	4 x 6" = 20, A4 = 10
	High Resolution Paper (HR-101N)	A4 = 65
	Photo Paper Plus Semi-Gloss (SG-201)	4 x 6"=20, A4, 8 x 10" = 10
	Envelope	Envelopes (DL, COM10, C5, Monarch) = 10
Paper Handling (Cassette 2: Lower) (Maximum Number)	Plain Paper	A4, Letter, Legal = 250
Paper Output	Approx. 75 pages (A4, Letter, Legal)	
Support Media for Auto 2-sided Printing	Type:	Plain Paper
	Size:	A4, Letter
Paper Weight	Cassette 1 (Upper):	Plain Paper: 64 - 105g/m <sup>2</sup> , Canon specialty paper: max paper weight: approx. 275g/m <sup>2</sup> (Photo Paper Plus Glossy II, PP-201)
	Cassette 2 (Lower):	Plain Paper: 64-105g/m <sup>2</sup>
Ink End Sensor	Electrical pulse detect + Dot count	
Print Head Alignment	Auto / Manual	
<b>Network</b>		
Protocol	SNMP (Standard MIB), TCP / IP	
Wired LAN	Network Type:	IEEE802.3u ?100BASE-

		TX?/ IEEE802.3 ?10BASE-T?
	Data Rate:	10M / 100Mbps (auto switchable)
Wireless LAN	Network Type:	IEEE802.11n / IEEE802.11g / IEEE802.11b
	Frequency Band:	2.4GHz
	Channel:	1 - 13
	Range:	indoor 50m (depends on the transmission speed and conditions)
	Security:	WEP64 / 128bit, WPA-PSK (TKIP / AES), WPA2-PSK (TKIP / AES)
Direct connection (Wireless LAN)	Available	
<b>Printing Solutions</b>		
Apple AirPrint	Available	
Layout	1-up (bordered only)	Letter, A4, 4 x 6", 5 x 7", 8 x 10", A5, B5, Legal, A6, Oficio, M-Oficio, Foolscap, Legal (India), Executive, Envelopes (DL, COM10, C5, Monarch)  Custom size [cassette (upper)]: width 89 - 216.0mm, length 127 - 355.6mm, [cassette (lower)]: width 210 - 216.0mm, length 279.4 - 355.6mm)
	Print Quality*3	Standard / High
Microsoft Mobile Print	Available	
Layout	1-up (bordered only)	Letter, A4, 4 x 6", 5 x 7", 8 x 10", A5, B5, Legal, Envelopes (DL, COM10)
	Print Quality*3	Standard / High
Mopria	Available	
Google Cloud Print	Available	
Canon Print Service Plugin	Available	

(for Android OS)		
PIXMA / MAXIFY Cloud Link	from smartphone or tablet:	Available
	from printer:	Available
Canon PRINT Inkjet / SELPHY (for iOS / for Android) Canon Easy- PhotoPrint (for Windows RT)	Available	
Layout	1-up (bordered only)	Letter, A4, 4 x 6", 5 x 7", 8 x 10", A5, B5, Legal, A6, Oficio, B-Oficio, M- Oficio, Foolscap, Legal (India), Executive
	Print Quality	Fixed
<b>System Requirements</b> (Please visit <a href="http://www.canon-asia.com">www.canon-asia.com</a> to check OS compatibility and to download the latest driver updates.)	Windows:	Windows 10, Windows 8, Windows 7 SP1, Windows Vista SP2
	Macintosh:	Mac OS X v10.8.5 and later
<b>General Specifications</b>		
Operation Panel	Display:	Full dot
	Language:	32 Languages Selectable: Japanese / English (mm & inch) / German / French / Italian / Spanish / Dutch / Portuguese / Norwegian / Swedish / Danish / Finnish / Russian / Czech / Hungarian / Polish / Slovene / Turkish / Greek / Simplified Chinese / Traditional Chinese / Korean / Indonesian / Slovak / Estonian / Latvian / Lithuanian / Ukrainian / Romanian / Bulgarian / Croatian / Vietnamese
Interface	USB B Port	USB 2.0 High Speed
Operating Environment <sup>*3</sup>	Temperature: 5 - 35°C Humidity: 10 - 90% RH (no dew condensation)	

Recommended Environment* <sup>4</sup>	Temperature: 15 - 30°C Humidity: 10 - 80% RH (no dew condensation)	
Storage Environment	Temperature: 0 - 40°C Humidity: 5 - 95% RH (no dew condensation)	
Quiet mode	Available	
Acoustic Noise (PC Print)	Document (A4, B / W, Default) * <sup>5</sup>	Approx. 56dB(A)
Power	AC 100 - 240V 50 / 60Hz	
Power Consumption	Standby (scanning lamp is off) USB connection to PC	Approx. 0.9W
	OFF	Approx. 0.3W
	Printing * <sup>6</sup> (USB connection to PC)	Approx. 27W
Typical Electricity Consumption (TEC)* <sup>7</sup>	Approx. 0.2kWh	
Environment	Regulation:	RoHS (EU, China)*, WEEE (EU)*  *To be fixed
	Eco-Label:	Energy Star*  *To be fixed
Duty Cycle	up to 30,000 pages/month	
Dimension (W x D x H)	Factory configuration	Approx. 463 x 394 x 290mm
	Paper installed (A4 / LTR)	Approx. 463 x 459 x 290mm
	Output / ADF trays extended	Approx. 463 x 607 x 290mm
Weight	Approx. 9.6kg	

Specifications are subject to change without notice.

- \*1 Document print speeds are the averages of ESAT in Office Category Test for the default simplex mode, ISO / IEC 24734. Document print speeds are the averages of FPOT in Office Category Test for the default simplex mode, ISO / IEC17629:2014  
Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.  
During successive printing, the printer may slow down the operation to prevent the internal temperature from rising.
- \*2 PPM print speed is based on the highest speed settings using Canon standard patterns on A4 plain paper.
- \*3 The performance of the printer may be reduced under certain temperature and humidity conditions.
- \*4 For the temperature and humidity conditions of papers such as photo paper, refer to the paper's packaging or the supplied instructions.
- \*5 Acoustic Noise is measured based on ISO7779 standard.
- \*6 Print: When printing ISO / JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings. Specifications are subject to change without notice.
- \*7 Typical Electricity Consumption (TEC) value: TEC value was calculated assuming the unit will be constantly switched among operational mode, sleep mode, and power-off mode for 5 days, and that it will be either in sleep or power-off mode for the remaining 2 days within the same week. The TEC value of this product is calculated by Canon on their own accord using TEC measurement procedure regulated in International ENERGY STAR Program.

#### Disclaimer

- Print speed becomes slower for the sake of preventing damage of a print head when ink draws to an end (after displaying the ink low message).
- An installed ink tank cannot be removed until the message to replace it is displayed.
- You need to install ink tanks or ink cartridges of all colours whether you perform black and white printing or colour printing. If any one of the ink tanks or ink cartridges is not installed, an error occurs and you cannot perform printing.
- Depending on the paper or the print settings, colour ink may be consumed even when you print a document in black or perform

printing in black and white. When any one of the colours of ink has run out, you need to replace the ink tank or ink cartridge.

- The printing costs described in the brochures or websites are based on the consumption data from not the first ink tank / ink cartridge but the succeeding ink tank / ink cartridge.
- To keep printer's performance, Canon printer performs cleaning automatically according to its condition. When the printer performs cleaning, a small amount of ink is consumed. In this case, all colours of ink may be consumed.  
[Cleaning function]  
The cleaning function helps the printer to suck air bubbles or ink itself from the nozzle and thus prevents print quality degradation or nozzle clogging.?
- The repairing parts for printers will be available five years after production is discontinued. Depending on your model, we may ask you to replace it with a new one, or one with almost the same performance as a maintenance service. In this case, it may be that you cannot use supplies or accessories for your model or the compatible OS will be changed.
- The warranty term for details, contact a Canon-authorized sales representative in the country or region you live in. Free repair does not apply to supplies (paper, ink tanks/cartridges, and print head) even within the warranty term.
- To obtain good printing quality, use up ink within six months after opening.
- Regarding a solution to a problem caused by using non-genuine ink cartridges (including ones supplemented with non-genuine ink by making a hole in the cartridge or so), a fee will be charged even within the warranty term. Keep this in your mind when you use non-genuine ink.
- If you use non-genuine ink cartridges (including ones supplemented with non-genuine ink by making a hole in the cartridge or so), they may have a negative effect on the performance of the printer or the printing quality may be reduced. In addition, though it is a rare case and does not present a safety hazard, it is reported that a print head will become heated or smoke will be emitted from it due to an ingredient not contained in genuine Canon ink. (Note that this does not apply to all non-genuine ink.)
- The following functions are available only on printers that use genuine Canon ink for all colors and support these functions. For supported functions, see the product specifications section for each model.
  - Printing CREATIVE PARK PREMIUM content via My Image Garden, Easy-PhotoPrint+, or PIXMA Cloud Link
  - Using the following applications via PIXMA Cloud Link
    - Scan to E-mail
    - Attach to Webmail
    - Scan to Office document
    - Scan and Remote Print



- Saving scanned images to Dropbox, Google Drive, OneDrive, Evernote, OneNote
  - Depending on your terminal, such as a computer or a smartphone, or the operating system of your terminal, such as your computer or smartphone, the estimated ink level information or message displayed on the screen of your terminal may be different from the information or message displayed on the operation panel of the printer. Also, a part of the estimated ink level message displayed on the operation panel of the printer may not be displayed and/or may be displayed at a different point in time. Canon recommends that you use the information and message displayed on the operation panel of the printer as your reference. Note, however, that such information and message are displayed items and serve only as a guideline information.
- 

- All prices above are recommended retail price in INR, unless otherwise stated.
- 

---

Copyright © 2019 Canon India Pvt Ltd. All rights reserved.

